SECTION 262813 – FUSES

PART 1 - GENERAL

1.1 RELATED DOCUMENTS

A. Drawings and general provisions of the Contract, including General and Supplementary Conditions and Division 01 Specification Sections, apply to this Section.

1.2 SUMMARY

- A. Section Includes:
 - 1. This Section specifies the fuses for buildings and structures.
 - 2. Provide all labor, materials, and equipment as necessary to complete all work as indicated on the drawings, and as specified herein for a complete operating system.
- B. Related Sections:
 - 1. Applicable sections of Division 26 Electrical

1.3 SUBMITTALS

- A. Shop Drawings
 - 1. Low-voltage fuses.

PART 2 - PRODUCTS

2.1 FUSES

- A. Fuses where required and/or specified for electrical equipment shall be Bussmann Fusetrons or equal by Littelfuse.
- B. Where fused disconnect switches are used protect for wire protection fuses shall be sized to protect the wire and be furnished for the disconnect switches.
- C. Fuses sized for motor protection shall be furnished for all combination starters. (Not greater than 125% of motor nameplate rating.)
- D. Fuses sized as shown on drawings shall be installed in all non-motor starter switches of motor control centers.

262813Fuses.docx Rev. 01/01/2009 PART 3 - EXECUTION

Not used.

END OF SECTION 262813