׬× SCALE: 3"=1'-0" **EXPANSION JOINT AT EXISTING PAVEMENT** BORE HOLE IN EXISTING CONCRETE PROVIDE #5 @ 18" LONG EPOXY-COATED DOWEL 4 À ۵ 1/4" TOOLED RADIUS EXISTING PAVEMENT EDGE
SHALL BE SAWCUT FULL DEPTH,
EXISTING EXPANSION JOINT OR
EXISTING CONSTRUCTION JOINT Ķ AA 1" GAP TO ALLOW FOR CONTRACTION OF CONCRETE REINFORCEMENT MESH, AS SPECIFIED SPEED DOWEL #5 @ 9" LONG, CENTER VERTICALLY WITHIN CONCRETE, SPACE 24" O.C. OR AS NOTED ON PLAN PROVIDE SUBMITTAL FOR DOWEL ASSEMBLY JOINT FILLER FULL DEPTH, HOLD DOWN 1/2" 1/2" ASPHALT EXPANSION CONCRETE MANUFACTURER: AS SPECIFIED SEE SPECIFICATION SECTION
321313 CONCRETE PAVEMENT

EXPANSION JOINT AT EXISTING PAVING

Typical Detail

JOINT_EXISTING_CONC.dwg

/14/10 INTHER

09

MICHIGAN STATE UNIVERSITY

Infrastructure Planning and Facilities