

APPROXIMATE PAVEMENT GRINDING PATTERN PARALLEL TO CURB

GRIND TO BE SLIGHTLY BELOW PAVEMENT TO PROTECT THERMOPLASTIC FROM BEING WORN


USE WHERE BIKE PATH IS IN THE ROAD

ALL SYMBOLS SHALL BE CENTERED IN BIKE PATH AND MAINTAIN A MINIMUM DISTANCE OF 6" FROM ANY ADJACENT PAVEMENT MARKINGS

SYMBOLS MARKING THE BEGINNING OF THE BIKE PATH SHALL BE EVEN WITH THE START OF BIKE PATH STRIPING

THE SYMBOLS MARKING THE END OF THE BIKE PATH SHALL BE EVEN WITH THE END OF BIKE PATH STRIPING

LAYOUT THERMOPLASTIC PIECES EXACTLY AS SHOWN



THERMOPLASTIC BIKE SYMBOL FOR ROAD USE

SCALE: 1/2"=1'-0"

SEE SPECIFICATION SECTION 321723 PAVEMENT MARKINGS

OF ONE	SHEET	REVISION	DATE
	DETAIL NO.	DATE	DATE
	321723-04	07/25/12	1/9/09
		JCUN/THFR	
		DRAWN	